

2016 **CART**

Enduro National Championships at Hallett Motor Racing Circuit October 7th - 9th, 2016

Presented By:





Sponsored By:

OFFICIAL PRE-ENTRY FORM


NAME	AGE KART MEN	MBER #				
ADDRESS	CITY	ST	ZIP			
KART RULE: PROOF OF CURRENT KART MEME JOIN. WEEKEND MEMBERSHIPS WILL NOT BE AVAIL	=	@ REGISTRAT	TON OR YO	OU MUST		
Passes: Driver \$30.00 Non-participant \$25.00 Children	ren (5-11) \$15.00 Childre	en Under 5 Free	(Purchase (@ Front Gate)		
ENTRY FEE: \$85.00 per class (\$90 @ T	rack) Friday pra	actice \$75.00				
CLASS NAME:	KART #	TRANS	PONDER #			
CLASS NAME:	KART #	TRANSF	PONDER #			
CLASS NAME:	KART #	TRANSF	PONDER #			
CLASS NAME:	KART #	TRANSF	PONDER #			
	13	NTRY FEES	@ \$8	35.00 \$		
FRIDAY PRACTICE @ \$75.00 \$						
	TRANSPO	TRANSPONDER RENTAL @ \$10.00 \$				
			TOTA	\L \$		
Pre-registration is recommended, full refunds available Please make checks payable and send pre-ent KART/MARRS - 24995 S. Meadow Ridge - Cla Credit Cards will be accepted with a \$5 proce	ries to: remore, OK. 74019	ostmark deadling	e for pre-reg	istration is Sept. 30th.		
I have read and hereby agree to conform and comply with MARRS, HALLETT MOTOR RACING CIRCUIT, their any loss, injury or death to myself, my family, or my pers understand that I will be responsible for myself and any n not covered by this event insurance or through any other in	agents, representatives, a onal property which may on-participants with me f	uthorized officia occur as a result	ils or track pe	ersonnel for		
ENTRANT SIGNATURE						
IF UNDER 18, PARENT SIGNATURE				-		
CDEC	IAL NOTICE					

SPECIAL NOTICE

Gates will be open 5:00-10:00 p.m. Thurs. Oct. 6th for Trailer Drop off, Pit Passes. If you arrive after 10:00 p.m. Thursday, you will be unable to enter the track until 6:00 a.m. Friday, when the gate will re-open.

Area motels: Hampton Inn

7852 W. Parkway Blvd Tulsa, OK 74127 918-245-8500 Boomtown Inn 1103 E. Broadway Drumright, OK 74030 918-352-2288 Best Western 211 Lake Drive Sand Springs, OK 74063 888-734-8507



2016

Enduro National Championships Hallett Motor Racing Circuit October 7th - 9th, 2016

Presented By:







JUNIOR (Age 8-11) ENTRY FORM

NAME	_AGE	_KART MEMBER	#		
ADDRESS	_CITY		_ ST	ZIP_	
KART RULE: PROOF OF CURRENT KART MEMIJOIN. WEEKEND MEMBERSHIPS WILL NOT BE AVAIL		REQUIRED @ REC	GISTRATI	ON OR	YOU MUST
Passes: Driver \$30.00 Non-participant \$25.00 Child	ren (5-11) \$	15.00 Children Und	er 5 Free	(Purchas	e @ Front Gate)
ENTRY FEE: \$50.00 per class		Friday practice \$20.00			
CLASS NAME:		KART #	TRANSP	ONDER # _	
CLASS NAME:	H	KART #	TRANSPO	ONDER#_	
CLASS NAME:	H	<art #<="" td=""><td> TRANSPO</td><td>ONDER # _</td><td></td></art>	TRANSPO	ONDER # _	
CLASS NAME:	H	KART #	TRANSPO	ONDER # _	
	ENTRY FEES @ \$50.00 \$				
					\$20.00 \$
		TRANSPONDER R	ENTAL	@	\$10.00 \$
				TC	OTAL \$
Pre-registration is recommended, full refunds available Please make checks payable and send pre-ent KART/MARRS - 24995 S. Meadow Ridge - Classification Credit Cards will be accepted with a \$5 process.	ries to: aremore, Ok		c deadline	for pre-re	egistration is Sept 30th.
I have read and hereby agree to conform and comply with MARRS, HALLETT MOTOR RACING CIRCUIT, their any loss, injury or death to myself, my family, or my persunderstand that I will be responsible for myself and any not covered by this event insurance or through any other	r agents, repr sonal proper on-participa	resentatives, authoriz ty which may occur a ants with me for any a	ed official as a result o	s or track	personnel for
ENTRANT SIGNATURE					
IF UNDER 18, PARENT SIGNATURE					
SPEC	CIAL NOTIC	F			

Gates will be open 5:00-10:00 p.m. Thurs. Oct th for Trailer Drop off, Pit Passes. If you arrive after 10:00 p.m. Thursday, you will be unable to enter the track until 6:00 a.m. Friday, when the gate will re-open.


Area motels: Hampton Inn

7852 W. Parkway Blvd Tulsa, OK 74127

918-245-8500


Boomtown Inn 1103 E. Broadway Drumright, OK 74030 918-352-2288

Best Western 211 Lake Drive Sand Springs, OK 74063 888-734-8507





Enduro National Championships Hallett Motor Racing Circuit October 7th - 9th, 2016



EVENT SCHEDULE

THURSDAY

5:00 - 10:00: TRAILER DROP OFF / PIT PASS SALES

FRIDAY

6:00: GATES OPEN

7:00 - 5:00: REGISTRATION

8:00: DRIVERS MEETING

9:00 - 3:00 - PAID PRACTICE (LUNCH 12:00-1:00)

3:15: RACE 1 (30/45 MIN)

SPRINT TAG LITE Fosters 4J Racing

YAMAHA PIPE HEAVY (410#) West Texas Kartways

3:15: RACE 2 (30 MIN)

BEST DRIVER Who Dat Racing

SATURDAY

6:00: GATES OPEN

7:30: DRIVERS MEETING

8:15-11:00: PRACTICE

11:00 - 11:45: LUNCH

12:00: RACE 3 (30 MIN)

SPRINT STOCK LEOPARD I Fosters 4J Racing

SPRINT ROTAX SR I Lifetime Roofing

12:45: RACE 4 (45 MIN)

SPORTSMAN I Proto Type Specialties

YAMAHA 4-HOLE CAN I Renegade Fuel Company

1:45: RACE 5 (30 MIN)

SPRINT CIK YAMAHA I McZero Fabrication

B&S ANIMAL SPORTSMAN I A.W. Henry Inc

B&S ANIMAL 390 I

SPRINT B&S LO206 I Gharst Family Racing

2:30: RACE 6 (30 MIN)

**SPRINT TAG JR I (12-15) Gharst Family Racing SPRINT TAG CADET I (8-11) Team Jake Racing

3:15: RACE 7 (30 MIN)

SPRINT TAG SR I West Texas Outlaws

SPRINT 80cc SHIFTER I Rick Learning Construction LLC

4:00: RACE 8 (30 MIN)

SPRINT 125cc SHIFTER I Cypert's Auto LLC

**SPRINT 125cc STOCK HONDA I 2R Racing

4:45: RACE 9 (45 MIN)

100cc OPEN J&E Automotive

PISTON PORT I Jess & Jim's Steakhouse





SUNDAY

6:00: GATES OPEN

7:00: KARTERS FOR CHRIST

7:30: DRIVERS MEETING

7:45-10:15: PRACTICE

10:30: RACE 10 (45 MIN)

UNLIMITED Everhart Racing

A-LIMITED Styled Aesthetic LLC

PISTON PORT II Gharst Family Racing

11:15 - 12:00: LUNCH

12:15: RACE 11 (30 MIN)

SPRINT STOCK LEOPARD II Land Survey Companies SPRINT ROTAX SR II Lifetime Roofing

1:00: RACE 12 (30 MIN)

SPRINT CIK YAMAHA II McZero Fabrication B&S ANIMAL SPORTSMAN II Kittelson Racing

B&S ANIMAL 390 II

SPRINT B&S LO206 II Karters for Christ

1:45: RACE 13 (30 MIN)

SPRINT 125cc SHIFTER II Gharst Family Racing

**SPRINT 125cc STOCK HONDA II Serta Mattress

2:30: RACE 14 (30 MIN)

**SPRINT TAG JR II (12-15) HMRC

SPRINT TAG CADÈT II (8-11) Gharst Family Racing

3:15: RACE 15 (30 MIN)

SPRINT TAG SR II Fisher Racing Engines SPRINT 80cc SHIFTER II Iron Will Racing

4:00: RACE 16 (45 MIN)

SPORTSMAN II Tanda Racing YAMAHA 4-HOLE CAN II MKA

IF THERE ARE ANY ENTRIES FOR SPRINT TAG JR OR SPRINT YAMAHA JR THEY WILL RUN IN RACE #6 AND RACE #14

6:00: JOIN US FOR SATURDAY AWARDS CEREMONY FOR FOOD AND BEVERAGES SUPPLIED BY MARRS **SUNDAY AWARDS WILL FOLLOW 15 MINS AFTER** POST TECH HAS CONCLUDED IN REGISTRATION BUILDING

NOTE: THURSDAY - SATURDAY: GATES CLOSE AT 10:00pm.

2016 LOCAL OPTION CLASS RULES

ALL CLASSES: NO ETHANOL IS ALLOWED. CHASSIS AND MOTOR SPECS PER 2016 KART RULES

BEST DRIVER:

All Senior Classes, 7 laps counted, best consistent time wins (must turn within 1 second of normal lap times), Scoring starts sometime after 2nd completed lap, No triad will be awards for this class. Winner will be announced Saturday at Awards banquet. \$50 entry fee.

YAMAHA PIPE HEAVY:

16+, 410#, gas/oil, Yamaha engine, max. 1.75" header and any fixed pipe (no adjustable pipes)

SPRINT TAG SR. LIGHT:

16+, gas/oil, weights: PRD FIREBALL – 350#, LEOPARD – 360#, ROTAX 375#, X30 – 385#. **EVO NOT APPROVED**.

SPRINT YAMAHA JR:

8-11, 230#, gas/oil, Yamaha engine, WA55B carb, SSX or SSX-V muffler.

SPRINT 4-CYCLE JR:

8-12, gas, LO206: Green slide, 240#, Chonda: Purple slide, 235#

SPRINT TAG JR:

12-15, gas/oil, Leopard/Rotax Max/PRD Fireball: 320#, X-30: 330#
RESTRICTORS: Leopard - 25mm (1A-A-125366) exhaust header restrictor, PRD Fireball - RLV
30.0mm exhaust header restrictor, X-30 - 31.0mm (IAME Jr header pipe) exhaust header restrictor. Rotax Max – Per USRMC Jr. Rules.

SPRINT 125 cc STOCK HONDA:

Age: 16+

Weight: 385#

Fuel: Gas/oil

- A.1. This set of rules provides engine and chassis rules for the KART Road Race National Championships.
- A.2. Guidelines offered in these pages are subject to the term "Spirit and Intent" and apply to the technical aspects of this "Stock" shifter kart class. It is expected that all participants will adhere to the spirit and intent of these rules. These are guidelines for fair and equitable competition. They are not the basis to "read between the lines" in order to circumvent the intent.

 Spirit and Intent: "If these paragraphs do not say you can, you can't!"
- A.3. Stock Defined: All displacements will bear a tolerance that will be defined by specifications deemed as "Factory Stock," in specifications from said manufacturer. All post event technical inspection will rely on published factory specifications and may be compared to known stock parts. Neither the OEM engine nor any of its auxiliary components may be modified in any way, unless an exception and / or exclusion is specifically noted within the rules. This includes the addition, deletion and / or omission of and / or adjustment to parts and / or materials. Note: Adjustments to components that are specifically designed for that purpose shall not be construed to be a modification (i.e. Carburetor jets, needles, slides, adjustment screws, spark plugs, exhaust flange spacers, etc.)
- A.4. OEM Defined: For purposes of defining allowable engine components, OEM will mean parts produced by a particular manufacturer for a particular model. Where OEM parts are called out for example, you may not use Yamaha parts in a Honda engine, or Honda RS parts in a Honda CR engine. Except where otherwise stated, the year of manufacture is open, provided the parts are commercially available in the U.S. market.
- A.5. Engine: Stock 1997 2002 OEM Honda CR125 kit engine.
- A.6. Cylinder and Top End: 1997-2002 cylinders are legal. No modification or machining of the cylinder is allowed such as porting, adding or deleting ports, decking of top or bottom of cylinder, or re-Nikasil. Cylinder mounting flanges may be spot faced in the area where the nut meets the flange only. Some factory grinding is performed prior to the Nikasil process on many cylinders. The Technical Director reserves the right to disapprove any cylinder supplied by Honda and not modified. Some OEM cylinders may not be acceptable for competition.

Cylinder length is: 1997 – 1999: 3.311" - 3.316". 2000 – 2002: 3.307" – 3.312". Base gasket to be stock OEM.

Exceptions: Stock power valves may be removed and aftermarket plugs used, with no filing, welding, or modifying of the cylinder. The power valve actuator rod hole may be plugged. OEM power valve covers may be replaced with aftermarket plates.

Cylinder Head: Head must remain OEM with no modifications or machining of any kind. Head must fit factory profile using the Shockwave "Stock CR125" profile gauge. Removal of mounting boss and modifications to the water outlets, for the purpose of hose connection, are allowed.

Head gasket must be stock OEM.

Squish or deck height measurement through the spark plug hole will be a minimum of .050 thousandths for 1997 – 1999 and .045 for 2000 - 2002, using .060 solder. This is not intended to be a minimum or maximum dimension. This dimension is a "quick" check to determine if any non-conforming modifications are present.

Piston, Ring, Wristpin: Piston, ring, wristpin and upper rod bearing must be stock OEM. No modifications of any kind. Lapping the bottom of the ring is permitted.

A.7. Intake System:

Carburetor: Box stock PWM or PWK 38mm carburetor. Bore may not exceed 38.6mm in diameter. Carburetor bore measurement will be determined at the engine side of the slide. Bore may not exceed the designated maximum diameter in an area .400" wide measured inboard of the slide.

Fuel Pump: Pump around fuel recirculation system is allowed. Single, pulse type pump feed system. One (1) feed pump only. Any additional pump must be for evacuation (i.e. pump around system). No electric or belt driven pumps. Catch containers and / or alternative plumbing are mandatory, to deal with potential carburetor overflow.

Manifold and reeds: Intake manifold must be stock 1999 OEM CR125 (Honda Part Number 16221-KZ4-A10 - marked KZM4) with no modifications. The reed cage must be 1999 CR125 (Honda Part Number 14100-KZ4-J11) Aftermarket replacement reeds will be allowed, including mono reeds or stiffeners. This only allows reeds that may be installed without modification to the 1999 reed cage and does not permit multi-stage reeds.

Intake Noise Suppression: Air box or air filter only. Air box with NO modifications, up to 3 inlet tubes, not to exceed 29mm +/-1mm inside diameter & 95mm minimum length and must be CIK and RLV approved only).

A.8. Ignition System:

CDI: Must be stock 1999 OEM. Note: The wires connecting the coil and stator to the CDI may be lengthened or replaced, to facilitate mounting of the CDI unit. The addition and use of a coil ground cable is recommended. Kill switch, if used, must function only to kill the engine. The spark plug wire and cap are non-tech items.

Note: The events officials may require competitors to swap CDI boxes, prior to the start of a race event. Failure to comply will result in disqualification for the day.

Stator/Flywheel: Must be stock 1999 OEM. Only repairs approved by the Technical Director may be done to the wiring. Stock flywheel key must remain in place with no modifications. The left hand lower limiting plate on the stator must be intact, with no modification. Either the factory limiting plate or SKUSA limiting plate (available from SKUSA) may be used. Machined aluminum stator slots, underneath unmodified limiting plates, are allowed at this time. No modification to the hold down bolts is permitted. Static timing must be controlled by the stock stator plate or the SKUSA plate. No modification to any of the components that change the static timing.

The spark plug manufacturer is open, but the plug must be commercially available and measure 18.5mm long by pitch M14 x 1.25. Exception: The spark plug washer may be removed to facilitate the use of a cylinder head temperature sensor and the gap of the electrode may be adjusted.

- Coil: Must be OEM 1999 with no modifications.
- A.9. Exhaust Pipe: R4 or SKUSA SK-1 pipe only. Must be intact at post-tech.
- A.10. Exhaust Silencer: Make and mfg are open specs. Must be intact at post-tech. Must meet sound requirements.
- A.11. Transmission: Five (5 speed) as originally delivered in motorcycles or six (6) speed available through Honda in kit form.
- A.12. Clutch: Must be OEM with NO modifications.

Note: While air / electric / pneumatic shifters are not allowed, this restriction may be waived to accommodate special driver needs and requires prior written approval. Use of a sprag axle hub assembly is permitted.

- A.13. Cooling System: One of the water outlets in the cylinder head may be plugged. Note: The stock water outlet(s) must remain in the original location, in relation to the exhaust port. OEM water pumps must be retained. No axle or external water pumps allowed. Cooling system may use only water and / or water based coolants. The size and routing of the cooling hose(s) is open. Catch containers and / or alternative plumbing is mandatory, to deal with potential radiator overflow.
- A.14. External Modifications: Cases must be stock OEM. Exception(s): Kick-starter assembly may be removed and the hole plugged. Removal of the kick-starter hump is allowed. The case may be clearanced to accept a larger front drive gear.
- A.15. Other: Studs, bolts and washers are non-tech. Accessory mounting brackets and locations are open. Chain guards are required (steel is recommended).